CURVE TENT *400 - 1.750 CM*



TECHNICAL DATA

STANDARD VERSION				
Span	400 cm	500 cm	1.250 cm	1.750 cm
Side height	230 cm	240 cm	310 cm	300 cm
Ridge height	373 cm	395 cm	640 cm	640 cm
Roof pitch	20°	25°	18°	18°
Bay distance / grid	300 cm	500 cm	300 cm	300 cm
Main profile	94 x 48 x 3 mm	130 x 70 x 3 mm	220 x 100 x 3 mm	220 x 100 x 3 mm
Max. windspeed according to EN	100 km/h			
Floor	· Wooden floor · Heavy-duty floor · Compact floor			
Tarpaulin	RÖDER No. 1, PVDF coated tarpaulin, according to DIN 18204			

EMAS VERIFIED ENVIRONMENTAL MANAGEMENT DE-129-00032

ISO 9001 ISO 14001 DVS ZERT EN 1090

CURVE TENT *400/230/373 & 500/240/395*





CURVE TENT *1.250/310/640 & 1.750/300/640*







QUESTIONS AND COMMENTS

We have summarized the most important data and dimensions of our standard constructions for you. All information is without guarantee. No liability is assumed for printing and spelling errors. We would be happy to advise you personally about the optimal construction for your needs. Your Röder team is at your disposal to answer any questions you may have about intermediates, special features, conversions and other technical data.